




**DECLARATION OF PERFORMANCE**  
**DoP-1007-130701**

**Fortrac**  
**40/40-35 T**



EN 13249 EN 13250 EN 13251 EN 13253 EN 13254 EN 13255 EN 13257 EN 13265

**Intended function(s): Reinforcement**

**HUESKER Synthetic GmbH**  
**Fabrikstraße 13–15**  
**48712 Gescher, Deutschland**  
**Tel. +49 (0) 25 42 / 701 - 0**  
**Fax. +49 (0) 25 42 / 701 – 499**  
**E-Mail: info@HUESKER.de**  
**Factory A**

System 2+

**Notified factory production control certification body No. 0799 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control on the system 2 + and issued the certificate of conformity of the factory production control.**

Essential characteristics	Performance	Harmonised technical specification
Tensile strength $T_{max}$ (EN ISO 10319)	MD 40 kN/m (- 0 kN/m) CMD 40 kN/m (- 0 kN/m)	EN13249:2000 + A1:2005 EN13250:2000 + A1:2005
Elongation $\epsilon_{max}$ (EN ISO 10319)	MD 8,5 % ( $\pm$ 1,5 %) CMD 8,5 % ( $\pm$ 1,5 %)	EN13251:2000 + A1:2005 EN13253:2000 + A1:2005
Durability (Annex B)	To be covered within 30 days after installation.  Predicted to be durable for a minimum of 25 years in natural spills with $4 < pH < 9$ and a soil temperatures $< 25^{\circ}C$ .	EN13254:2000 + A1:2005 EN13255:2000 + A1:2005 EN13257:2000 + A1:2005 EN13265:2000 + A1:2005

Gescher 01.07.2013

\_\_\_\_\_  
**Helko Pintz**  
(Manager Quality Assurance)