




DECLARATION OF PERFORMANCE
DoP-1029-130701

Fortrac
R 200/30-30 T



Intended function(s): Reinforcement

HUESKER Synthetic GmbH
Fabrikstraße 13–15
48712 Gescher, Deutschland
Tel. +49 (0) 25 42 / 701 - 0
Fax. +49 (0) 25 42 / 701 – 499
E-Mail: info@HUESKER.de
Factory A

System 2+

Notified factory production control certification body No. 0799 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control on the system 2 + and issued the certificate of conformity of the factory production control.

Essential characteristics	Performance	Harmonised technical specification
Tensile strength T_{max} (EN ISO 10319)	MD 200 kN/m (- 0 kN/m) CMD 30 kN/m (- 0 kN/m)	EN13249:2000 + A1:2005 EN13250:2000 + A1:2005
Elongation ϵ_{max} (EN ISO 10319)	MD 8,5 % (\pm 1,5 %) CMD 9 % (\pm 2 %)	EN13251:2000 + A1:2005 EN13253:2000 + A1:2005
Durability (Annex B)	To be covered within 30 days after installation. Predicted to be durable for a minimum of 25 years in natural soils with $4 < pH < 9$ and a soil temperatures $< 25^{\circ}C$.	EN13254:2000 + A1:2005 EN13255:2000 + A1:2005 EN13257:2000 + A1:2005 EN13265:2000 + A1:2005

Gescher 01.07.2013

Helko Pintz
(Manager Quality Assurance)